

Philips
PAL coax cable

2 m

> 75 dB Male-Female

SWV2818W



Ensure a reliable connection

with this PAL coax cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality

- Nickel-plated connectors for reliable contact

Enjoy good audio quality

- High-purity copper conductor for reliable signal transfer

Protects against signal loss

- Bare copper shielding

Easy installation

- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Moulded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

PAL coax cable
2 m > 75 dB Male-Female

Specifications

Packaging dimensions

- **Packaging dimensions (W x H x D):**
9.4 x 23.6 x 3.6 cm
- **Net weight:** 0.098 kg
- **Gross weight:** 0.120 kg
- **Tare weight:** 0.022 kg
- **EAN:** 87 12581 37989 6
- **Number of products included:** 1
- **Packaging type:** Blister

Outer Box

- **Outer carton (L x W x H):** 33.3 x 25.7 x 17.8 cm
- **Net weight:** 1.176 kg

- **Gross weight:** 2.020 kg
- **Tare weight:** 0.844 kg
- **EAN:** 87 12581 37991 9
- **Number of consumer packages:** 12

Inner Box

- **Inner carton (L x W x H):** 24.4 x 10.4 x 15.7 cm
- **Net weight:** 0.392 kg
- **Gross weight:** 0.560 kg
- **Tare weight:** 0.168 kg
- **EAN:** 87 12581 37990 2
- **Number of consumer packages:** 4

SWV2818W/I0

Product highlights

Bare copper shielding

Bare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Flexible PVC Jacket

Flexible PVC jacket provides protection to the delicate core of the cable. It also offers extended durability and ease of installation.

High-purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Moulded plug

Moulded plugs ensure secure connections between components and offer extended durability.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Rubber strain relief

Rubber strain relief provides a secure yet flexible juncture between the cable and the plug.



Issue date 2009-02-16

Version: 1.0.9

12 NC: 8670 000 35447
EAN: 87 12581 37989 6

© 2009 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com